

Features

- Low forward voltage drop
- Soft recovery
- Hermetic metal cases with ceramic insulators

I_{F(AV)} **3560A**
V_{RRM} **1100~2000V**
t_{rr} **7.0μs**

Typical Applications

- Inverters and choppers
- Motor control
- Snubber and free-wheeling diodes



SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T _j (°C)	VALUE			UNIT
				Min	Type	Max	
I _{F(AV)}	Mean forward current	180° half sine wave 50Hz Double side cooled,	150			3560	A
V _{RRM}	Repetitive peak reverse voltage	tp=10ms	150	1100		2000	V
I _{RRM}	Repetitive peak current	at V _{RRM}	150			240	mA
I _{FSM}	Surge forward current	10ms half sine wave V _R =0.6V _{RRM}	150			44	kA
I ² t	I ² t for fusing coordination					9680	A ² s*10 ³
V _{FO}	Threshold voltage		150			0.95	V
r _F	Forward slope resistance					0.10	mΩ
V _{FM}	Peak forward voltage	I _{TM} =5000A, F=40kN	25			3.00	V
I _{rm}	Reverse recovery current	I _{TM} =2000A, tp=1000μs, -di/dt=20A/μs, V _R =50V	150			310	A
t _{rr}	Reverse recovery time					7	μs
Q _{rr}	Recovery charge					1100	1300
R _{th(j-c)}	Thermal resistance Junction to case	At 180° sine double side cooled Clamping force 40kN				0.010	°C /W
R _{th(c-h)}	Thermal resistance case to heat sink					0.003	
F _m	Mounting force					35	
T _{stg}	Stored temperature					-40	
W _t	Weight					1100	
Outline	ZT73ct						

Outline

